

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

**IN THE CLAIMS**

Please amend the claims as follows, substituting any amended claim(s) for the corresponding pending claim(s):

1. (Currently Amended) An apparatus for designing a memory configuration for use in an embedded processing system, the apparatus comprising:

a processing system, the processing system comprising:

a simulation controller capable of simulating execution of a program to be executed by said embedded processing system;

a memory access monitor capable of monitoring, during said simulated execution of said program, memory accesses to a simulated memory space, wherein said memory access monitor is capable of generating memory usage statistical data associated with said monitored memory accesses, and wherein said memory accesses comprise read operations and write operations; and

a memory optimization controller capable of ~~comparing~~ using said memory usage statistical data, a memory model, and one or more design criteria associated with said embedded processing system and, ~~in response to said comparison, determining~~ to determine at least one memory configuration capable of satisfying said one or more design criteria,

wherein said memory model includes, for each of a plurality of memory types, one or more characteristics selected from write power, refresh power, read power, area per bit, area efficiency, write speed, read speed, erase capability and block size, and

wherein said one or more design criteria are selected from memory type usage constraints.

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

memory type size constraints, memory power consumption objectives, and memory speed objectives.

2. (Previously Presented) The apparatus as set forth in Claim 1 wherein said at least one memory configuration is determined from a set of memory types, said set of memory types comprising at least two of static random access memory (SRAM), dynamic random access memory (DRAM), read-only memory (ROM), flash RAM (FLASH), and electronically erasable programmable read-only memory (EEPROM).

3. (Original) The apparatus as set forth in Claim 2 wherein said at least one memory configuration comprises a first memory type and a first memory size associated with said first memory type.

4. (Original) The apparatus as set forth in Claim 3 wherein said at least one memory configuration further comprises a second memory type and a second memory size associated with said second memory type.

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

5. (Previously Presented) The apparatus as set forth in Claim 1 wherein said simulation controller simulates execution of said program N times and wherein said memory access monitor monitors said memory accesses during said N simulated executions of said program and generates said memory usage statistical data based on said N simulated executions of said program.

6. (Previously Presented) The apparatus as set forth in Claim 1 wherein said memory optimization controller is further capable of determining at least one figure of merit associated with said at least one memory configuration, wherein said at least one figure of merit indicates a degree to which said at least one memory configuration satisfies said one or more design criteria.

7. (Currently Amended) The apparatus as set forth in Claim 1 further comprising a code optimization controller capable of automatically modifying said program in response to said ~~comparison~~ use of said memory usage statistical data, said memory model and said one or more design criteria to thereby enable said embedded processing system to execute said program according to said one or more design criteria.

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

8. (Currently Amended) A method of designing a memory configuration for use in an embedded processing system, the method comprising the steps of:

simulating execution of a program to be executed by the embedded processing system;

monitoring, during the simulated execution of the program, memory accesses to a simulated memory space, wherein said memory accesses comprise read operations and write operations;

generating memory usage statistical data associated with the monitored memory accesses;

~~comparing using~~ the memory usage statistical data, a memory model and one or more design criteria associated with the embedded processing system; ~~and~~

~~in response to the comparison, determining~~ to determine at least one memory configuration capable of satisfying the one or more design criteria,

wherein the memory model includes, for each of a plurality of memory types, one or more characteristics selected from write power, refresh power, read power, area per bit, area efficiency, write speed, read speed, erase capability and block size, and

wherein the one or more design criteria are selected from memory type usage constraints, memory type size constraints, memory power consumption objectives, and memory speed objectives.

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

9. (Previously Presented) The method as set forth in Claim 8 wherein the at least one memory configuration is determined from a set of memory types, the set of memory types comprising at least two of static random access memory (SRAM), dynamic random access memory (DRAM), read-only memory (ROM), flash RAM (FLASH), and electronically erasable programmable read-only memory (EEPROM).

10. (Original) The method as set forth in Claim 9 wherein the at least one memory configuration comprises a first memory type and a first memory size associated with the first memory type.

11. (Original) The method as set forth in Claim 10 wherein the at least one memory configuration further comprises a second memory type and a second memory size associated with the second memory type.

12. (Previously Presented) The method as set forth in Claim 8 wherein the step of simulating execution of the program comprises the sub-steps of simulating execution of the program N times, wherein the step of monitoring the memory accesses comprises the sub-steps of monitoring the memory accesses during the N simulated executions of the program, and wherein the step of generating the memory usage statistical data is based on the N simulated executions of the program.

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

13. (Previously Presented) The method as set forth in Claim 8 further comprising the step of determining at least one figure of merit associated with the at least one memory configuration, wherein the at least one figure of merit indicates a degree to which the at least one memory configuration satisfies the one or more design criteria.

14. (Currently Amended) The method as set forth in Claim 8 further comprising the step of automatically modifying the program in response to the ~~comparison~~ usage of the memory usage statistical data, the memory model and the one or more design criteria to thereby enable the embedded processing system to execute the program according to the one or more design criteria.

15. (Previously Presented) An embedded processing system comprising a memory configuration designed according to the method as set forth in Claim 8.

16. (Previously Presented) An embedded processing system comprising a memory configuration designed according to the method as set forth in Claim 9.

17. (Previously Presented) An embedded processing system comprising a memory configuration designed according to the method as set forth in Claim 10.

**DOCKET NO. 99-B-186 (STMI01-99186)**  
**SERIAL NO. 09/591,621**  
**PATENT**

18. (Previously Presented) An embedded processing system comprising a memory configuration designed according to the method as set forth in Claim 11.

19. (Previously Presented) An embedded processing system comprising a memory configuration designed according to the method as set forth in Claim 12.

20. (Previously Presented) An embedded processing system comprising a memory configuration designed according to the method as set forth in Claim 13.

21. (Previously Presented) An embedded processing system comprising a memory configuration designed according to the method as set forth in Claim 14.

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

22. (Currently Amended) For use in a processing system, a computer-readable storage medium containing computer-executable instructions for designing a memory configuration for use in an embedded processing system, the computer-executable instructions comprising the steps of:

simulating execution of a program to be executed by the embedded processing system;

monitoring, during the simulated execution of the program, memory accesses to a simulated memory space, wherein said memory accesses comprise read operations and write operations;

generating memory usage statistical data associated with the monitored memory accesses;

~~comparing using the memory usage statistical data, a memory model and one or more design~~  
criteria associated with the embedded processing system; and

~~in response to the comparison, determining to determine at least one memory~~  
configuration capable of satisfying the one or more design criteria,

wherein the memory model includes, for each of a plurality of memory types, one or more characteristics selected from write power, refresh power, read power, area per bit, area efficiency, write speed, read speed, erase capability and block size, and

wherein the one or more design criteria are selected from memory type usage constraints, memory type size constraints, memory power consumption objectives, and memory speed objectives.



DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

23. (Previously Presented) The computer-readable storage medium as set forth in Claim 22 wherein the at least one memory configuration is determined from a set of memory types, the set of memory types comprising at least two of static random access memory (SRAM), dynamic random access memory (DRAM), read-only memory (ROM), flash RAM (FLASH), and electronically erasable programmable read-only memory (EEPROM).

24. (Original) The computer-readable storage medium as set forth in Claim 23 wherein the at least one memory configuration comprises a first memory type and a first memory size associated with the first memory type.

25. (Original) The computer-readable storage medium as set forth in Claim 24 wherein the at least one memory configuration further comprises a second memory type and a second memory size associated with the second memory type.

26. (Previously Presented) The computer-readable storage medium as set forth in Claim 22 wherein the step of simulating execution of the program comprises the sub-steps of simulating execution of the program N times, wherein the step of monitoring the memory accesses comprises the sub-steps of monitoring the memory accesses during the N simulated executions of the program, and wherein the step of generating the memory usage statistical data is based on the N simulated executions of the program.

DOCKET NO. 99-B-186 (STMI01-99186)  
SERIAL NO. 09/591,621  
PATENT

27. (Previously Presented) The computer-readable storage medium as set forth in Claim 22 further comprising the step of determining at least one figure of merit associated with the at least one memory configuration, wherein the at least one figure of merit indicates a degree to which the at least one memory configuration satisfies the one or more design criteria.

28. (Currently Amended) The computer-readable storage medium as set forth in Claim 22 further comprising the step of automatically modifying the program in response to the ~~comparison~~ usage of the memory usage statistical data, the memory model and the one or more design criteria to thereby enable the embedded processing system to execute the program according to the one or more design criteria.

29. (Previously Presented) The apparatus of Claim 1, wherein the memory usage statistical data comprises at least one of:

one or more first histograms based on variable names contained in the program to be executed by the embedded processing system; and

one or more second histograms based on memory locations accessed by the program to be executed by the embedded processing system.